

## FLOOR & WALL OPENINGS

- |   | yes                      | no                       |
|---|--------------------------|--------------------------|
| Are floor openings guarded by a cover, guardrail, or equivalent on all sides (except at entrance to stairways or ladders)?  | <input type="checkbox"/> | <input type="checkbox"/> |
| Are toeboards installed around the edges of a permanent floor opening (where persons may pass below the opening)?   | <input type="checkbox"/> | <input type="checkbox"/> |
| Are skylight screens of such construction and mounting that they will withstand a load of at least 200 pounds?  | <input type="checkbox"/> | <input type="checkbox"/> |
| Is the glass in windows, doors, glass walls, which are subject to human impact, of sufficient thickness and type for the condition of use?  | <input type="checkbox"/> | <input type="checkbox"/> |
| Are grates or similar covers over floor openings, such as floor drains, of such design that foot traffic or rolling equipment will not be affected by the grate spacing?                            | <input type="checkbox"/> | <input type="checkbox"/> |
| Are unused portions of service pits and pits not actually in use either covered or protected by guardrails or equivalent?   | <input type="checkbox"/> | <input type="checkbox"/> |
| Are manhole covers, plus their supports, designed to carry a truck rear axle load of at least 20,000 pounds when located in roadways and subject to vehicle traffic?                                | <input type="checkbox"/> | <input type="checkbox"/> |
| Are floor or wall openings in fire resistive construction provided with doors or covers compatible with the fire rating of the structure, and provided with self-closing features when appropriate? | <input type="checkbox"/> | <input type="checkbox"/> |